

MS Series Remote Accessories

The MS Series remote accessories are designed to be used with the Air Products and Controls Duct Smoke Detectors to provide audible and visual indication as well as remote test/ reset functions. These devices are constructed of attractive, yet durable brushed stainless steel and mount on a standard single or double gang electrical backbox.

Wiring Diagram

Specification

	Pilot LED (Green)	Alarm LED (Red)	Fault Trouble LED (Yellow)	Push Button Test/ Rest	Key Operated Test/Reset	Horn	Single Gang	Double Gang
MS-RA		Yes					Yes	
MS-RA/P	Yes	Yes					Yes	
MS-RA/R		Yes		Yes			Yes	
MS-RA/P/R	Yes	Yes		Yes			Yes	
MS-RA/P/T	Yes		Yes				Yes	
MS-RA/FT/P	Yes		Yes	Yes			Yes	
MS-KA/R		Yes			Yes		Yes	
MS-KA/P/R	Yes	Yes			Yes		Yes	
MS-KA/P/R/T	Yes		Yes		Yes		Yes	
MS-RD		Yes					Yes	
MS-F/T			Yes				Yes	
MS-RH/P/A	Yes	Yes				Yes	Yes	
MS-RH/KA/P/R	Yes	Yes			Yes	Yes		Yes
MS-RH/KA/P/A/T	Yes	Yes	Yes		Yes	Yes		Yes
MS-RH						Yes	Yes	
Power Requirements:	Alarm LED Trouble LED Pilot LED Alarm Horn	15mA @ 24 VDC 15mA @ 24 VDC 15mA @ 24 VDC 20mA @ 24 VDC						
Sound Pressure:	Alarm Horn	78dB @ 10ft.						
Dimensions:	Single Gang Double Gang	4 1/2" H x 2 3/4" W 4 1/2" H x 4 1/2" W						
Wiring:	LEDs/Horn Switches	6" / 24 AWG Pigtails 6" / 22 AWG Pigtails						
Approvals	UL Listed for use with air products and controls duct smoke detectors including all RW-Series, SM-Series and SL-Series duct smoke detectors. UL URRQ. S7425 ULC URRQ7. S7425 CSFM 7300-1004:107 MEA 73-92-E VOL25							

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK **T:** +44 (0)345 894 7000 **E:** enquiries@advancedco.com
W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.