

SSPKWLP Series

The Gentex SSPK24WLP Series are wall mount, selectable candela speaker/strobes designed to meet code requirements for audio, visual and voice communications. The SSPK24WLP Series are quality speaker products that offer both dependable evacuation signaling and visual alarms, or a combination of both. The high output tamperproof candela selections are 15, 30, 60, 75, 110. A fixed 15/75 candela unit is also available.

The SSPK24WLP can be mounted in a 4" square x 2-1/8" deep back box, an extension ring is not needed.

The SSPK24WLP Series provides a 25 or 70.7 VRMS speaker with field selectable power taps of 1/8W, 1/4W, 1/2W, 1W, 2W or 4W. The SSPK24WLP strobes can be synchronized by using the Gentex Synchronization Control Module, FACP's or power supplies that include the Gentex Synchronization Protocol.

The SSPK24WLP Series grills are constructed of high impact textured plastic.

The SSPK24WLP is warranted for 3 years from the date of purchase. The SSPK24WLP devices are UL listed for fire protective services per UL 1480, the selectable candela strobe unit is listed to UL 1971, and the 15/75 unit is listed to UL 1638 and UL 1971.

Low Profile Evacuation Speakers and Speak/Strobes

Model Number	Description	Part Number
28-SSPKCLPR	Speaker	904-1445-002
28-SSPKCLPW	Speaker	904-1446-002
28-SSPK24WLPR	Speaker/Strobe	904-1413-002
28-SSPK24WLPW	Speaker/Strobe	904-1415-002
28-SSPK24-15/75WLPR	Speaker/Strobe	904-1417-002
28-SSPK24-15/75WLPW	Speaker/Strobe	904-1419-002

Speaker dBA @ 10 ft.

Input Watts	25 Volts	70.7 Volts
1/8	74.6 dBA	73.7 dBA
1/4	77.7 dBA	76.7 dBA
1/2	80.5 dBA	79.6 dBA
1	83.1 dBA	82.5 dBA
2	85.6 dBA	85.4 dBA
4	87.9 dBA	87.9 dBA

Note: The SSPK24WLP Series is not listed for outdoor use. Operating temperature: 32° to 120°F (0° to 49° C). Gentex does not recommend using a coded or pulsing signaling circuit with any of our strobe products (see technical bulletin number 014). "R" = Red Faceplate, "W" = Off-White Faceplate, "P" = Plain (no lettering) Available with all models.

Features

Tamperproof Selectable Candela 15, 30 60, 75 and 110
Fixed 15/75 Candela
High-Quality dBA Output (Intelligible)
Frequency Range 400-4000Hz
Tamperproof Grill
Unit Dimensions: 6.1" Square x 1.88" Deep
Wall Mounting to Standard 4" x 2 1/8" Deep Back Box
Field Selectable Power Taps 1/8, 1/4, 1/2, 1, 2, 4 Watt
Speaker Voltage 25 or 70.7 VRMS Standard, Field Selectable
Faceplate Available in Red or Off-White

Listings and Approvals

UL Listed: 138, 1971 and 1480
MEA: 580-06-E
CSFM:
7320-0569:140 (SSPK24WLP Series)
7320-0569:137 (SSPKCLP Series)

SSPK24WLP Wall Mount Strobe Current Ratings

Candela	15cd	30cd	60cd	75cd	110cd	15/75
24 VDC	55mA	63mA	88mA	112mA	136mA	63mA
UL Max ¹	78mA	96mA	137mA	180mA	224mA	96mA

1 RMS current ratings are per UL average RMS method. UL maximum current rating is the maximum RMS current within the listed voltage range (16-33VDC for 24VDC units) (8-17VDC for 12VDC units). For strobes, the UL max current is usually at the minimum listed voltage (16VDC for 24VDC units) (8VDC for 12VDC units). For audibles, the maximum current is usually at the maximum listed voltage. For unfiltered FWR ratings, see installation manual.

Wiring Diagram

Specification

The fire alarm speaker shall be Gentex SSPK24WLP or equivalent. The speaker shall be capable of producing alarm tones or voice on all 25 or 70.7 VRMS audio systems. The speaker shall provide incremental tap settings of 1/8, 1/4, 1/2, 1, 2 or 4 watts. Minimum 1/4 watt shall be 76.7 dBA and at 4 watts 87.9 dBA. Tap settings shall be adjustable with field selectable jumper pins. The speaker shall also have an operational visual signal capability.

The visual signal shall have 1Hz flash rate regardless of input voltage. All field wiring connections shall be made via separate in-out terminal connections and the speaker, or speaker strobe shall be UL, CSFM and BS&A/MEA listed and compliant with all local, state and federal fire alarm codes/standards.

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK **T:** +44 (0)345 894 7000 **E:** enquiries@advancedco.com
W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.