

Wall Mounting Single Relay Output Module

The single channel output modules are loop-powered, designed around a fully digital protocol and provide form C changeover contacts for activating equipment for DDA compliance such as vibrating pillows.

The output channel is a normally de-energised relay switched on by a command from the control panel.

The unit provides a fast and secure response, and incorporates a bidirectional short circuit isolator.

Connections are made using plug-in terminal blocks which will accept conductors up to 2.5mm².

The unit is supplied fixed to a plate which is suitable for wall mounting with a choice of standard 25 mm or deep 47 mm mounting boxes available.

Features

Short circuit isolators in each device to the requirements of EN54-17

Auto-addressing capability (by the control panel) or manually using a hand held programmer.

Digital checking of double address

Line quality information

Bicolour (red/green) LED driven by the control panel

Standards and Approvals

EN54-17:2005

EN54-18:2005

Specification

Power supply	15 - 40 Vdc
Maximum alarm current consumption	6 mA
Relay switching	2 A / 30 Vdc
Operating temperature range	-30°C to +70°C
Humidity (non condensing)	85% RH
Dimensions H x W x D mm	87 x 87 x 32
Weight	200 g
IP rating	21C

Order Codes and Options

20-VMC120-ADV:	Wall Mounting Single Relay Output Module
----------------	--

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK **T:** +44 (0)345 894 7000 **E:** enquiries@advancedco.com
W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.