

2-8 Loop Fire Alarm Control Panel

TheMxPro 5 series is fully expandable from 2 to 8 loops and supplied with 8 onboard sounder circuits, 20 programmable Zonal LEDs with slide-in labels, and 25 System LEDs for information purposes. There are also 8 programmable function buttons with LED indication for confirmation of operation.

The control panel consists of the latest dual flash-based microprocessor technology combined with a high resolution, high contrast, graphical LCD display and tactile keypad providing a simple select & click programming aid for engineer configuration and end-user operation.

Compatible with AdvancedLive (UK&I only), which is the fire panel monitoring solution that enables secure, easy, real-time management of an Advanced fire system.

Powerful cause-and-effect programming coupled with dynamic zoning and enhanced Trace Diagnostics makes the panel suitable for a wide range of site applications from small to large complex multi-area systems. Fully programmable onsite via the onboard alphanumeric keypad, or PC-Net-022 configuration software.

An extensive suite of user-friendly Windows-based PC software programs has been developed to enhance your experience when usingMxPro 5 series fire panels. The suite incorporates a number of different programmes to include a configuration, service and logo tool to allow greater flexibility of the equipment to be fully explored.

Simply adding a network card allows the panel to communicate with any otherMxPro 5/MxPro 4fire panel, remote terminal, or network peripherals, such as BMS or graphical interface. The network operates as a true peer-to-peer system and can be configured in a fault tolerant loop or radial format.

Features

Connectivity to AdvancedLive (UK&I only), Ethernet on-board
Fully expandable from 2 - 8 loops via plug-in loop driver cards.
20 programmable Zonal / 25 System LEDs with slide-in labels.

Apollo, Argus Vega, Hochiki & Nittan Evolution protocol support.

Advanced graphical LCD user interface and support for up to 200 fire zones by default allowing full EN54 compliance without additional hardware.

Dual flash-based microprocessor technology with real-time clock onboard.

Dedicated USB & RS232 serial port for direct PC or modem connection.

Installer friendly Auto-learn, Loop Detection and Onboard Scope facility for ease of commissioning and fault finding.

Fully programmable via the onboard alphanumeric keypad, or PC configuration tools.

The graphical display can be configured to operate with virtually any language or character set and allow the installer's logo to be applied using the Logo application software.

Robust removable equipment chassis with plug-in connectors for simple fixing and cable termination.

Integral P-Bus for system expansion via available option cards.

Advanced networking, peer-to-peer system, with up to 2000 zones.

Approvals

EN54-2:1997 +AC:1999 +A1:2006

EN54-4:1997 +AC:1999 +A1:2002 +A2:2006

EN 50130-4: 2011+A1:2014

EN 55032:2015

EN 62368-1:2014+A11:2017

EN 62368-1:2020+A11:2020

EN IEC 63000:2018

EN 54-13:2017 (Pending)

Specification

Base Technology	Dual flash-based processors with real-time clock, trace diagnostics, programmable languages and character sets
Display	White backlit 240 x 64 graphical LCD (5.5 inches x 2.5 inches)
LED Indicators	22 red (1 x Fire, 1 x More Alarms, 20 x Zonal Programmable), 1 green (Power), 13 amber and 7 bi-colour (Fault & System)
Controls	Alpha numeric keypad permitting Navigation, Reset, Mute, Silence, Resound, Evacuate, and 4 x Programmable Push Buttons
Protocols	Apollo (Soteria / XP95 / Discovery), Hochiki ESP, Argus Vega and Nittan Evolution
Number of Fire Zones	2000 when networked (400 max across 8 loops)
Number of loops	Dedicated 2-8 loop control panel
Devices per loop	Protocol dependent
Loop Current	500mA max per loop
On-Board Sounder Circuits	8 x 1 Amp programmable
On-Board Relays	4 x 1 Amp 30v AC/DC programmable (10mA, 5v min) - expandable to 8 using 2 x Mxp-507
Auxiliary Supply	2 x 24v 500mA 2
Programmable Input	2 x On-board Programmable Input
Programmable Key Switch Inputs	16 volt free digital inputs
Total Available Output Current	2 x 5A maximum available for loop current + sounder outputs + auxiliary supply
Mains Supply	200 - 240v 47-63 Hz AC (+10%, -15% tolerance) 1.4A max
Charger Current	2 x 2.0A temperature compensated
Ethernet port	10-Base-T, 100-Base-T: Providing AdvancedLive connectivity (UK&I)
Serial ports	2 x on-board RS232 connection for PC, modem, IP or portable printer
USB Interface	2 x USB B type connection for PC communication
Programming	On-board keypad or PC running Windows tools
Event Log	2 x 5000 Event & Diagnostic + 500 Fire
Enclosure / Colour	Steel IP30 / RAL7035
Temperature	-5°C to 40°C
Humidity (RH)	95% Max
Metalwork Options	Flushing bezel, battery box, utility enclosure, termination enclosure and rack mount

Dimensions and Capacity

	Dimensions	Cable Entry	Battery Capacity (internal)	
	H x W x D mm	(20mm knockouts)	Min	Max
Standard	750 x 450 x 190	30 x top, 6 x top rear, 2 x bottomrear & 3 x bottom	24v, 4Ah	24v, 45Ah*

*1 x 24V 45Ah internal (max) and 1 x 24V 45Ah external (max) using optional battery enclosure

Order Codes and Options

Network/Protocol	Apollo (XP95/Discovery) / Hochiki ESP	Apollo Soteria *	Argus Vega	Nittan Evolution
Standard	MX-5802	MX-5802A	MX-5802V	MX-5802N
Fault-Tolerant	MX-5802/FT	MX-5802A/FT	MX-5802V/FT	MX-5802N/FT

* MXP-568 is required

Note: 2 loops card come as standard. If more loops are required, please order 1 loop driver card per extra loop.

Part Code	Description
MXP-568	Loop driver card - Apollo, Hochiki, Argus Vega
MXP-567	Loop driver card - Nittan

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK **T:** +44 (0)345 894 7000 **E:** enquiries@advancedco.com
W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.