

Photoelectric Smoke Detector

The photoelectric smoke detector has been designed with a unique symmetrical chamber.

The chamber ensures optimum air entry from all directions and offers immunity to ambient light into the detectors.

A custom ASIC provides superior and reliable detection performance whilst reducing the problems of false alarms.

A patented moulding profile helps to enhance long term stability by removing airborne contamination before it can enter the sensing chamber.

Features

EN54-7 approved (Cert No. 603a/08)
Double dust trap protects the smoke chamber from contamination
Central LED providing 360-degree visibility
Magnetic test feature
Anti-Tamper locking feature
Robust and reliable
Unique range of Decorline finishes are available
One-year warranty
Part Number 20-AS1000-ADV

Specification

Operating Voltage	10-30V
Stand by Current	I=75 uA
Alarm Current	Ial=50mA
LED Current Consumption	Iled=6mA @24Vdc
Operating Temperature Range	-30°C / +70°C
Device Sensitivity	0.17db/m (3.8%/m)
Humidity (no condensing)	95% RH
Height with Base	54 mm
Diameter	110mm
Approvals / Certification	EN54-7 approved (Cert No. 603a/08)

Order Codes and Options

20-AS1000-ADV:	Photoelectric Smoke Detector
----------------	------------------------------

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK **T:** +44 (0)345 894 7000 **E:** enquiries@advancedco.com
W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.